



AQUACULTURE
FEED & EQUIPMENT

PRODUCT #
W21820

水陸兩用泵浦 AMPHIBIAN PUMP

特性：

1. 抽送兩用型，濾水網取下接上水管；可做陸上抽水機。
2. 水冷式冷卻，馬達長時間運轉也不發熱，葉輪切水原理經特殊設計，水量特大。

適用：

井水抽取，地下溪水，養殖漁業，農業灌溉，水利工程。

Features:

1. Available for delivery or extraction. Also it can be served as landed water pump can easily drain water.
2. Water cooling design. It will not over heat even in longtime operation. Impeller slicing system specially designed for extra large volume of water.


Usage:

To draw out well water, to suck ground water, Aquatic pond, Irrigation, hydraulic engineering.

規格 (Specification):

產品編號	馬力	相數	口徑	極數	揚程/水量(標準)		揚程/水量(最高)		電壓
PRODUCT #	OUTPUT (HP)	PHASE (Ø)	DISCHARGE (INCH)	POLE (N)	HEAD(M)/CAPACITY(GPM)(STANDARDS)	HEAD(M)/CAPACITY(GPM)(HIGH)	HEAD(M)/CAPACITY(GPM)(HIGH)	VOLTAGE (V)	
W21810	2	3Ø	2"	2	12	66	17	150	220
W21820	2	3Ø	2"	2	10	106	18	185	380
W21900	2	1Ø	3"	2	11	154	16	220	220
W22000	2	3Ø	3"	4	11	193	10	275	220
W22100	3	3Ø	4"	4	11	268	9.8	383	220
W22200	5	3Ø	4"	4	9	370	13	528	220
W22300	5	3Ø	5"	4	9	462	13	660	220

產品編號 Product #	W21820	產品名稱 (Product description)	
型號 (Item #)	TC232	2HP 3PH 2" SUBMERSIBLE PUMP	
馬力 OUTPUT	2 (HP)	極數	口徑
	POLE		DISCHARGE (INCH)
	2 (N)		2"
	電壓		相數
	VOLTAGE		PHASE
	380 (V)		3 (Ø)
	揚程 / 水量 (標準)		
	HEAD(M)/CAPACITY(GPM)(STANDARDS)		
	10		106
	揚程 / 水量 (最高)		
	HEAD(M)/CAPACITY(GPM)(HIGH)		
	18		185



(泵浦類)
PUMP

