



AQUACULTURE
FEED & EQUIPMENT

PRODUCT #
W45150

高揚程清水泵浦 SUPER HEAD PUMP

特性：

1. 密封式葉輪提高揚程及效率。
2. 馬達本體外筒，軸心，濾網，螺絲均採不銹鋼材質，美觀耐用。

適用：

草坪，花園，園藝灑水，噴水，果園灌溉，屋頂噴水；污水坑，廢水處理，抽井水，汽車清洗用水。

Features:

1. Closing vane impeller is designed for increased efficiency.
2. The Motor essence, shaft and screws are used Stainless Steel material.

Usage:

A sprinkler for grass, garden, horticulture, and irrigation for orchard, waste water, well water access, wash car, and sprayed water on the roof.

規格 (Specification):

產品編號	馬力	相數	口徑	極數	揚程 / 水量 (標準)		揚程 / 水量 (最高)		電壓
PRODUCT #	OUTPUT (HP)	PHASE (Ø)	DISCHARGE (INCH)	POLE (N)	HEAD(M)/CAPACITY(GPM)(STANDARDS)	HEAD(M)/CAPACITY(GPM)(HIGH)	HEAD(M)/CAPACITY(GPM)(HIGH)	VOLTAGE (V)	
W23120	2	1Ø	2"	2	18	36	26	52	220
W23130	2	3Ø	2"	2	18	36	26	75	220
W23150	3	1Ø	2"	2	25	74	35	105	220
W23160	3	3Ø	2"	2	25	74	35	105	220
W23200	3	1Ø	3"	2	21	92	30	132	220
W23210	3	3Ø	3"	2	21	92	30	132	220
W45150	5	3Ø	3"	2	21	186	30	265	220
W45160	7.5	3Ø	4"	2	25	224	36	264	220
W45170	10	3Ø	4"	2	28	315	40	450	220
W45200	15	3Ø	8"	4	14	1110	20	1585	220
W45250	20	3Ø	10"	4	14	1294	20	1849	220

產品編號 Product #	W45150	產品名稱 (Product description)	
型號 (Item #)	TH337	5HP 3PH 3"HIGH.HEAD.SUBMERSIBLE.PUMP	
馬力 OUTPUT	5 (HP)	口徑	極數
		DISCHARGE (INCH)	POLE
		3"	2 (N)
		相數	電壓
		PHASE	VOLTAGE
		3 (Ø)	220 (V)
		揚程 / 水量 (標準)	
		HEAD(M)/CAPACITY(GPM)(STANDARDS)	
		21	186
		揚程 / 水量 (最高)	
		HEAD(M)/CAPACITY(GPM)(HIGH)	
		30	265



(泵浦類)
PUMP

